

Declaration of Performance

DoP No. 004/CPR-2013-07-01

1. Product type: Outwards opening single side-hung exterior door without glazing
2. ID No.: DIPLOMAAT M10*21
3. Intended use: External pedestrian doorset in domestic and commercial locations
4. Manufacturer: Haapsalu Uksetehase AS, Masti tee 8, Uuemõisa 90401, Ridala vald, Lääne maakond, Estonia
5. Authorised representative: ./.
6. System of assessment and verification of constancy of performance: 3
7. Harmonised standard: EN 14351-1:2006 + A2:2016
8. Notified body: VTT No.0809 has carried out the Initial Type Testing in system 3 as a notified body, and has issued the test and classification reports
9. Essential characteristics

Essential characteristics	Performance	Harmonised standard
Watertightness	3A	EN 14351-1:2006 + A2:2016
Dangerous substances	-	
Resistance to wind load	C3	
Impact resistance	-	
Load-bearing capacity of safety devices	-	
Height	2011 mm	
Acoustic performance	Rw(C;Ctr)=27(-2;-1)	
Thermal transmittance *	0,81 W/m ² K	
Radiation properties		
-Solar factor <i>g</i>	-	
-Light transmittance <i>T_v</i>	-	
Air permeability	4	

*Calculation by No.0809

10. The performance of the product identified in points 1 and 2 conforms with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Rene Serg, R&D manager
Uuemõisa, 31.10.2017

