

Haapsalu Uksetehase AS  
 Masti 8  
 90401 Uuemõisa, Lääne mk.  
 Estonia



**EN 14351-1:2006+A2:2016**

Windows and doors- Product standard, performance characteristics - Part 1:  
 Windows and external pedestrian doorsets



Tüüp	Thermal transmittance Uw/Ud	Resistance to wind load	Air permeability	Watertightness	Acoustic performance	DoP
	[ W/m²/K ]					
IV78 fixed	0,89	C5	4	9A	Rw(C;Ctr)=32(-1;-6)	TD nr.001
IV78 openable	0,94	C5	4	9A	Rw(C;Ctr)=32(-1;-6)	TD nr.001
IV92 fixed	0,77	C5	4	E1050	Rw(C;Ctr)=33(-1;-7)	TD nr.002
IV92 openable	0,82	C5	4	E1050	Rw(C;Ctr)=33(-1;-7)	TD nr.002
MACO Panorama	0,83	C3	4	4A	Rw(C;Ctr)=26(-1;-6)	TD nr.006
Patio-Life	0,94	C3	4	4A	Rw(C;Ctr)=26(-1;-6)	TD nr.006
Facade window MEK	0,69	npd	npd	npd	Rw(C;Ctr)=33(-1;-7)	TD nr.007
Facade window MEK-alu	0,71	npd	npd	npd	Rw(C;Ctr)=33(-1;-7)	TD nr.008
Balcony door IV78	0,9	C5	4	5A	Rw(C;Ctr)=32(-1;-6)	TD nr.009
Dbl balcony door IV78	0,9	C3	4	4A	Rw(C;Ctr)=32(-1;-6)	TD nr.010
Ext Diplomaat	0,81	C3	4	3A	Rw(C;Ctr)=27(-2;-1)	TD nr.004
Ext Diplomaat 1PS	0,94	C3	4	3A	npd	TD nr.004
Ext EI30/Rw40dB Ex	0,98	C3	4	3A	Rw(C;Ctr)=40(-1;-4)	TD nr.005

npd - no performance determined